

POLYSELECT™ POWER DET

SURFACTANT

Description POLYSELECT™ POWER DET is a proprietary blend of surfactants for use in water based drilling fluids

Applications/Functions *The use of POLYSELECT™ POWER DET can promote the following:*

- Reduce clay and shale build up on bit
- Reduce sticking tendencies of clay and shale

Advantages

- Effective at low concentrations
- Easy to mix
- Reduces bit balling

Typical Properties

Appearance	Clear red liquid
Bulk Density, lb/ft ³	1.03
pH (1% solution)	8.9
Pour Point	28°F (-2.2°C)

Recommended Treatment

<i>Typical Amount of POLYSELECT™ POWER DET added to fluid system</i>			
Desired Condition/Result	Amount/100 gallons	Amount/bbl	Liters/m ³
Prevent bit balling	2 – 4 pints	1 – 2 pints	2 – 5 liters
Reduce stickiness of clay and shale	1 – 6 quarts	1 – 3 quarts	5 – 12 liters

Availability

To receive information regarding POLYSELECT™ POWER DET please contact our Customer Service Department either by phone, fax or email below:

Bentonite Performance Minerals, LLC.
A Halliburton Company
3000 N. Sam Houston Pkwy. E.
Houston, TX 77032
www.bentonite.com

Phone (281) 871-7900 Fax (281) 7423 Email fbpm@halliburton.com

© Copyright 2018 Halliburton. All Rights Reserved.
POLYSELECT™ is a trademark of Halliburton.

Rev. 10/2018

Because the conditions of use of this product are beyond the seller's control, the product is sold without warranty either express or implied and upon condition that purchaser make its own test to determine the suitability for purchaser's application. Purchaser assumes all risk of use and handling of this product. This product will be replaced if defective in manufacture or packaging or if damaged. Except for such replacement, seller is not liable for any damages caused by this product or its use. The statements and recommendations made herein are believed to be accurate. No guarantee of their accuracy is made, however.



BENTONITE

Performance Minerals LLC