

POLYSELECT™ POWER SODA ASH

Water Conditioner

Description POLYSELECT™ POWER SODA ASH water conditioner is designed to reduce the hardness and increase the pH of make-up water utilized for drilling fluids.

Applications/Functions *The use of POLYSELECT™ POWER SODA ASH can assist the following:*

- Reduce water hardness
- Increase pH

Advantages

- Improve yield and effectiveness of bentonite and polymer by precipitating calcium ions and raising the pH

Typical Properties

Appearance	White/off-white powder
pH (5% aqueous solution)	11.5
Bulk Density	57 - 65

Recommended Treatment Add 0.5 – 2 lb/100 gallons of POLYSELECT™ POWER SODA ASH slowly through the hopper prior to addition of bentonite or additives. pH range should be maintained at 8.5 - 9.5 for typical bentonite based fluids.

Availability To receive information regarding POLYSELECT™ POWER SODA ASH please contact our Customer Service Department either by phone, fax or email below.

Bentonite Performance Minerals, LLC.

A Halliburton Company

3000 N. Sam Houston Pkwy. E.

Houston, TX 77032

www.bentonite.com

Phone (281) 871-7900 Fax (281) 871-7423 Email fbpm@halliburton.com

© Copyright 2018 Halliburton. All Rights Reserved.
POLYSELECT™ is a trademark of Halliburton.

Rev. 10/2018

Because the conditions of use of this product are beyond the seller's control, the product is sold without warranty either express or implied and upon condition that purchaser make its own test to determine the suitability for purchaser's application. Purchaser assumes all risk of use and handling of this product. This product will be replaced if defective in manufacture or packaging or if damaged. Except for such replacement, seller is not liable for any damages caused by this product or its use. The statements and recommendations made herein are believed to be accurate. No guarantee of their accuracy is made, however.



BENTONITE
Performance Minerals LLC