

# POLYSELECT™ POWER THIN

## Thinner/Dispersant

**Description** POLYSELECT™ POWER THIN is a phosphate free drilling fluid thinner and dispersant. POLYSELECT™ POWER THIN quickly acts to break up sticky clays and alter rheology of water based fluids.

**Applications/Functions** *The use of POLYSELECT™ POWER THIN can assist the following:*

- Reduce bit balling and mud rings
- Reduce torque and drag in sticky clay formations
- Lower viscosity and gel strength of water based drilling fluids.

**Advantages**

- Easy to mix
- Effective at low concentrations
- Works quickly

**Typical Properties**

Appearance	Clear colorless to yellow liquid
------------	----------------------------------

**Recommended Treatment**

To reduce viscosity and gel strength, start by slowly adding 1 pint of POLYSELECT™ POWER THIN to 500 gallons of water based drilling fluid. If a greater reduction of viscosity and gel strength is still desired, add small amount of material slowly to fluid system until desired results is achieved.

To reduce mud rings or bit balling, add 1 pint of POLYSELECT™ POWER THIN to 100 gallons of drilling fluid.

**Availability**

To receive information regarding POLYSELECT™ POWER THIN please contact our Customer Service Department either by phone, fax or email below.

**Bentonite Performance Minerals, LLC.**  
**A Halliburton Company**  
3000 N. Sam Houston Pkwy. E.  
Houston, TX 77032

Phone (281) 7900 Fax (281) 871-7423 Email [fbpm@halliburton.com](mailto:fbpm@halliburton.com)

© Copyright 2018 Halliburton. All Rights Reserved.  
POLYSELECT™ is a trademark of Halliburton.

Rev. 12/2018

Because the conditions of use of this product are beyond the seller's control, the product is sold without warranty either express or implied and upon condition that purchaser make its own test to determine the suitability for purchaser's application. Purchaser assumes all risk of use and handling of this product. This product will be replaced if defective in manufacture or packaging or if damaged. Except for such replacement, seller is not liable for any damages caused by this product or its use. The statements and recommendations made herein are believed to be accurate. No guarantee of their accuracy is made, however.



**BENTONITE**  
*Performance Minerals LLC*